

SummaSketch® III

DESKTOP TABLETS



SummaSketch III Professional 12 x 18 in / 30.5 x 45.7 cm



SummaSketch III 12 x 12 in / 30.5 x 30.5 cm

The award-winning SummaSketch III comes with everything you need for fast and accurate digitizing, tracing, drawing, illustrating, cursor steering and menu picking with your CAD and graphics programs. SummaSketch III is compatible with over 400 software programs — more than any other tablet available today.

SummaSketch III features an ergonomic, wedge-shape design and tilt adjustment that makes working comfortable and non-fatiguing. A recessed template or artwork area and transparent overlay hold your work securely. A choice of pen stylus, 4-button or 16-button cursor allow you to select the best configuration for your needs. SummaSketch tablets provide high accuracy and proximity sensing of up to one-half inch, which means that you can trace images even through thick material. Standard equipment includes the tablet, your choice of cursor or pen, drivers and utilities, interface cables and more. With SummaSketch III, you're ready to go.

FEATURES

Flexibility and Performance

- Ergonomic tablet in two convenient sizes
- Choice of transducers — cursor or pen
- Broad software compatibility
- High accuracy and resolution
- Autodesk ADI, Microsoft Windows 95, 98, NT and 3.1 drivers (WinTab compliant)
- Wedge-shape design and tilt mechanism
- Template/artwork recessed area and overlay to secure work

Summagraphics®

SummaSketch® III

DESKTOP TABLETS

| | |
|------------------------------|---|
| Platform Support | PC |
| Software Drivers | Microsoft mouse emulation Microsoft Windows 3.x (WinTab compliant) Microsoft Windows 95 (WinTab compliant) Microsoft Windows 98 (WinTab compliant) Microsoft NT (WinTab compliant) Autodesk Device Interface (ADI) Diagnostic test and utility software |
| Hardware Interface | RS-232 serial |
| Accuracy | Standard accuracy ± 0.010 in/0.254 mm |
| Resolution | 2,540 lines per inch/100 lpmm |
| Proximity | ≤ 0.5 in/12.7 cm, traces through documents up to 1/2 inch thick |
| Technology | Electromagnetic |
| Output Formats | Industry-standard MM (SummaSketch) and Microgrid UIOF |
| Operating Modes | Point, switch, switched stream, remote request |
| Power Supply | 100/110 volt, 220/240 volt wall mount power supply plugged into serial cable |
| Power Requirements | 12 volts DC, 200 mA current draw |
| Certification | FCC-B, CE |
| Operating Temperature | 50 to 104°F/10 to 40°C |
| Storage Temperature | -40 to +158°F/-40 to +70°C |
| Humidity Range | 0 to 95%, noncondensing |
| Operating Altitude | Up to 50,000 ft/15,200 m |
| Storage Altitude | Up to 50,000 ft/15,200 m |
| Warranty | One-year warranty |

Tablet Options and Physical Dimensions

| Model | Active Area | Width | Depth | Height (front) | Height (back) | Weight |
|--------|-------------------------|-----------------|-----------------|----------------|---------------|--------------|
| SS3-12 | 12 x 12 in/305 x 305 mm | 16.25 in/413 mm | 16.38 in/416 mm | .82 in/21 mm | 1.63 in/42 mm | 8 lb/3.7 kg |
| SS3-18 | 12 x 18 in/305 x 457 mm | 23 in/584 mm | 17.5 in/445 mm | .82 in/21 mm | 1.63 in/42 mm | 16 lb/7.4 kg |

Included With Your Purchase

- SummaSketch III tablet
- Choice of 4-button cursor, 2-button stylus or 16-button cursor
- CD ROM with TabletWorks software drivers, utility disk and user's manual
- Power supply
- Interface cable

Distributed by:

GTCO CalComp
PERIPHERALS

GTCO CalComp Inc.

14555 N. 82nd Street ▪ Scottsdale, AZ 85260

Voice 480.443.2480 ▪ Fax 480.948.5508

Toll Free USA, Canada 800-458-5888

Europe +43 (1) 7007 36450

E-mail summa.sales@gtcocalcomp.com

www.gtcocalcomp.com

Continuing research and development may result in specification or appearance changes at any time.

Summagraphics, Summagrid and TabletWorks are trademarks of GTCO CalComp Inc. All other product names are trademarks or registered trademarks of their respective owners.

Order No. SG5-899 Printed in U.S.A.

©1999 GTCO CalComp Inc. All rights reserved.



**MIAMI
MICRO
DATA**

4806 S.W. 74th Court, Miami, FL 33155

Voice: 800-853-2767
305-669-3006

Fax: 305-669-9314

www.miamimicro.com • sales@miamimicro.com